

Republic of the Philippines  
**PHILIPPINE SCIENCE HIGH SCHOOL-BICOL REGION CAMPUS**  
Tagongtong, Goa, Camarines Sur

**BID BULLETIN NO.1**

**Procurement of Construction of Property Building (Design and Build)**

January 3, 2021

This Supplemental /Bid Bulletin No. 1 is issued to amend information in the bid documents as regards bid opening:

1. Due to an urgent need to conduct disinfection activities in the campus from January 4-6, 2021, BAC has decided to postpone or re-schedule the bid opening for the above-cited project, supposedly scheduled January 5, 2021. It has been moved to **January 7, 2021 at 10AM.**
2. This notice of postponement is being issued in accordance with Section 29 of Revised IRR of RA 9184 and not for the purposes of delay.

For the guidance and information of all concerned.



SEVEDEO J. MALATE  
Chairperson, BAC

TECHNICAL SPECIFICATIONS FOR TECHNICAL AND SCIENTIFIC EQUIPMENT LOTS 2,3,and 4

<b>2</b>	<b>Robotics and Engineering Equipment</b>	<b>11</b>	<b>Educational Robotics Kit</b>	
				Main controller brick – Bluetooth and WIFI enabled with data logging; with at least 4 input and output ports
				Rechargeable battery with charger
				Interactive Servo motors (at least two with built-in rotation motors)
				Sensors (ultrasonic, touch, gyro, color)
				Building bricks and other elements for creating a vast variety of models with building instructions and software
		<b>12</b>	<b>Microcontroller Kits, peripherals, sensors</b>	
				Arduino official starter kit
				Powerboost 500 shield - rechargeable 5v Power Shield ADAFRUIT
				Battery lithium ion 3.7v 2000mah
				Accelerometer magnetometer gyroscope temp 9-dof breakout board lsm9ds0
				Battery 9v dc jack
				9v Battery
				Relay module 10a 2 channel
				Xbee shield
				Official raspberry pi power supply
				Gprs gsm sim800c shield for arduino
				Gps ultimate breakout 66 channel 10 hz updates version 3 adafruit
				Rs pro multimeter kit
<b>2</b>	<b>FABLAB/AdTech Tools and Equipment</b>	<b>13</b>	<b>Jigsaw</b>	Capacity: Wood 65mm (2-5/8") Capacity: Mild Steel Plate 6mm (1/4") Capacity: Min. Cutting Radius 25mm (1") Base Tilt Angle 45° Right/Left Power Input 400W Length of Stroke 18mm (45/64") No-Load Speed(stroke) 0-3,000/min. Overall Length 197mm (7-3/4") Weight 1.5kg (4.2 lbs.)
		<b>14</b>	<b>Planer</b>	Continuous rating Input: 750W Planing width: 82mm (3-1/4") Planing depth: 3mm (1/8") No load speed (rpm): 18,000

				<p>Dimensions (L x W x H): 390x175x140mm  Net Weight: 4.9kg (10.8lbs)  Power supply cord: 2.0m (6.6ft)</p>																		
		15	<b>Table Saw</b>	<p>Continuous rating Input: 1,500W  Max cutting capacity: at 0 degrees : 91mm (3-9/16")  at 45 degrees : 63mm (2-1/2")  Blade diameter: 255mm (10")  No load speed (rpm): 4,300  Dimensions (L x W x H): 726x984x333mm  Net Weight: 34.1kg (75.2lbs)</p>																		
		16	<b>Vacuum Cleaner</b>	<table> <tr> <td>Rated power input</td> <td>1,250 W</td> </tr> <tr> <td>Weight</td> <td>10 kg</td> </tr> <tr> <td>Max Vacuum Pressure (Turbine)</td> <td>200 mbar</td> </tr> <tr> <td>Max volume rate</td> <td>63 l/sec</td> </tr> <tr> <td>Dust Class</td> <td>L</td> </tr> <tr> <td>Container volume gross</td> <td>25 liters</td> </tr> <tr> <td></td> <td>480 x 380 x</td> </tr> <tr> <td>Tool dimensions (LxWxH)</td> <td>453mm</td> </tr> <tr> <td>Container volume net</td> <td>21 L</td> </tr> </table>	Rated power input	1,250 W	Weight	10 kg	Max Vacuum Pressure (Turbine)	200 mbar	Max volume rate	63 l/sec	Dust Class	L	Container volume gross	25 liters		480 x 380 x	Tool dimensions (LxWxH)	453mm	Container volume net	21 L
Rated power input	1,250 W																					
Weight	10 kg																					
Max Vacuum Pressure (Turbine)	200 mbar																					
Max volume rate	63 l/sec																					
Dust Class	L																					
Container volume gross	25 liters																					
	480 x 380 x																					
Tool dimensions (LxWxH)	453mm																					
Container volume net	21 L																					
		17	<b>Portable Belt Sander</b>	<table> <tr> <td>Rated Power Input(W)</td> <td>1200</td> </tr> <tr> <td>Belt Speed(m/min)</td> <td>500</td> </tr> <tr> <td>Belt Size(mm)</td> <td>100 x 610</td> </tr> <tr> <td>Net Weight(kg)</td> <td>5.8</td> </tr> </table>	Rated Power Input(W)	1200	Belt Speed(m/min)	500	Belt Size(mm)	100 x 610	Net Weight(kg)	5.8										
Rated Power Input(W)	1200																					
Belt Speed(m/min)	500																					
Belt Size(mm)	100 x 610																					
Net Weight(kg)	5.8																					
		18	<b>Stationary Belt Sander</b>	<p>Power: 375 Watts  Belt Size: 915 x 102mm  Disc Size: 150mm (6")  Voltage: 220V / 60hz</p>																		
		19	<b>Assorted Tools</b>	<p><b>Claw Hammer:</b> Wooden Handle  <b>Ball Pein hammer:</b> Wooden Handle  <b>File set for rotary tool:</b> 10pcs Set  <b>Cross Cut Saw:</b> Handle offers a square/mitre feature with 45° and 90° angles  <b>Hack Saw:</b> Large, comfortable tension knob for quick &amp; easy blade change  <b>Steel Ruler 30 cm:</b> Corner Style: rounded  <b>Steel Ruler 1 meter:</b> Material Type: Steel  <b>Drill bits set:</b> for wood and metal  <b>Jigsaw blade set:</b> for wood and metal  <b>Grinder disc set:</b> for wood and metal  <b>Mallet:</b> tough rubber head molded to a wood handle</p>																		
		20	<b>Miter Saw</b>	<p>Thumb actuated miter stops for quick and easy adjustment  Soft Grip  Large table  Equipped with chip deflector</p>																		



				<p><b>Gloves</b> Size Range: 36-46 COTTON GLOVES WITH LATEX</p> <p><b>Respirator</b> Advanced silicone material Provides at least 95% filtration efficiency</p> <p><b>Welding Apron</b> Leather with Sleeves</p> <p><b>Welding Goggles</b> Wear with head strap or as a spectacle. With Rubber Nose Cushion for comfort</p> <p><b>Fire Extinguisher</b> 10lbs capacity Dry chemical A.B.C. powder type Non - toxic Non - conducting and Non - corrosive chemicals Portable Type ISO Certified</p>
		29	<b>Jointer</b>	<p>1500 w (2Hp) 230v 60Hz Blade width 8" (203mm) 1/2" (12.7mm max) Cutting depth 1/2" (12.7mm max) Rabbeting cap max) Speed 4400 rpm 1315 x 395 Table (LxW) mm Height from floor 805mm Fence 875 x 98mm Tilt in and out 45°</p>
		30	<b>Workbench</b>	<p>Adjustable height - dual height Durable steel frame with anti-slip rubber feet Mobile - easy storage and transport and folds flat Dual clamping cranks increase clamping force and versatility Heavyweight steel construction allows support of 250kg Vice Jaw opening: 0 to 136 mm Vice jaw length: 740 mm</p>
		31	<b>Thickness Planer</b>	<p>Continuous rating Input: 1,650W Cutting width: 304mm (12") Cutting depth: Cutting width 0-150 mm : 3mm (1/8") Cutting width 150-240 mm : 1.5mm (1/16") Feed rate/min.: 8.5m (27.9ft) Table size (W x L): 304 x 771mm (12" x 30-3/8") No load speed (rpm): 8,500</p>
		32	<b>Sewing Machines</b>	<p>600 stitches including letters for any fabric Stitch sequencing with memory Consistent buttonholes with 13 one-step buttonhole styles</p>

				<p>Convenient stitch selector with stitch style/width/length preview Mirror Imaging Built-In Needle Threader (+)</p> <p>Top Drop In Bobbin (+) Built-In Thread Cutter (+) Thread Cutter Shut Off (+) Tie-Off Button (+) Drop Feed (+) Direct Selection Stitches (+) Adjustable Stitch Length (+) Adjustable Stitch Width (7mm) Self-Adjusting Tension System (+) Reverse (Touch Button) Heavy Duty Metal Frame (+) High Speed Stitching (850/min) Speed Control (Mechanical) Needle Up/Down (+) Programmable Needle Up/Down (+) LCD Screen (+) Free Arm (+) Extension Table Included (+) Snap-On Presser Feet (+) Extra High Pressor Foot Lifter (+) Variable Needle Positions (25) Twin-Needle Function (+) Machine Size (17.2 x 8.2 x 12)</p>
		33	<b>Router Table</b>	<p>24" x 32" router table top includes a router insert plate with three molded Level-Loc reducing rings 36" T-square style router table fence features a micro-adjust wheel for precise setups Outfeed anchor has been redesigned for more usable table space and easier removal Multi-purpose steel stand is adjustable from 31" to 39" in height Includes Router Table Top with insert plate, Router Table Fence and Multi-Purpose Steel Stand. #148166 KREG 4pc Casters Set not included.</p>
		34	<b>Portable/ Battery Powered drill</b>	<p>Torque, max. (hard screwdriving applications) 39 Nm No-load speed (1st gear/2nd gear) 0 - 450 / 1400 rpm Max. impact rate 19,500 bpm Chuck clamping range 10 mm Battery voltage 18 V Weight incl. battery 1.4 kg Torque settings 20+1</p> <p><b>Drilling diameter</b> Max. drilling diameter in wood 29 mm Max. drilling diameter in steel 10 mm</p>

				<p>Max. drilling diameter in masonry 10 mm</p> <p><b>Screw diameter</b></p> <p>Max. screw diameter 8 mm</p> <p>Integrated LED for lighting up work area</p> <p>Forward / Reverse rotation</p>
		35	<b>Portable/Battery Powered Drill Driver</b>	<p>Capacity: Machine screw : M4 - M8 (5/32" - 5/16")</p> <p>Standard bolt : M5 - M14 (3/16" - 9/16")</p> <p>High tensile bolt : M5 - M12 (3/16" - 1/2")</p> <p>Coarse thread (in length) : 22 - 125mm (7/8" - 4-7/8")</p> <p>Driving shank (Hex): 6.35mm (1/4")</p> <p>Impacts per minute (ipm): 0-3,200</p> <p>No load speed (rpm): 0-2,300</p> <p>Max. fastening torque: 150N.m (1,330in.lbs)</p> <p>Dimensions (L x W x H): 145x79x235mm (5-3/4"x3-1/8"x9-1/4")</p> <p>Net Weight: 1.3kg (2.9lbs)</p>
		36	<b>Digital Oscilloscope</b>	<p>Number of Channels 2</p> <p>Bandwidth 200MHz</p> <p>Oscilloscope Type Digital Storage</p> <p>Power Source Mains</p> <p>Display Type TFT LCD</p> <p>Minimum Vertical Sensitivity 1mV/div</p> <p>Maximum Vertical Sensitivity 10V/div</p> <p>Minimum Time Base 1ns/div</p> <p>Screen Size 8in</p> <p>Sample Rate Random 2 GSa/s, 100 GSa/s</p> <p>Rise Time 1.75ns</p> <p>Safety Category</p> <p>Safety Category Voltage 300V</p> <p>Vertical Resolution 8 bit</p> <p>Model Number p IDS2202A</p> <p>Plug Type Europe, UK</p> <p>Safety Category Level CAT I, CAT II</p>
		37	<b>Digital Signal Generator</b>	<p>Maximum Frequency Range 6GHz</p> <p>Sinewave</p> <p>Minimum Frequency Range 950kHz</p> <p>Sinewave</p> <p>Minimum Frequency Range 950 kHz</p> <p>Square Pulse and Arbitrary Waveform</p> <p>Digital Frequency Yes</p> <p>Digital Amplitude and Offset Yes</p> <p>Internal and External Yes</p> <p>Amplitude Modulation</p> <p>FM Modulation Yes</p> <p>Time Base Accuracy &lt;math&gt;\pm 0.5\text{ppm}&lt;/math&gt;</p> <p>Input Impedance 50 <math>\Omega</math></p>

				<p>Weight 5.4kg</p> <p>Frequency Range Square Pulse and Arbitrary 950 kHz → 6 GHz</p> <p>Waveform</p> <p>Minimum Operating Temperature +5°C</p> <p>Attenuation -130dB</p> <p>Interface Type Ethernet, GPIB, RS232, USB</p> <p>Dimensions 347 x 216 x 114mm</p> <p>Maximum Operating Temperature +40°C</p> <p>Width 216mm</p> <p>Length 347mm</p> <p>Model Number p TSG4106A</p> <p>Output Impedance 50Ω</p>
		<b>38</b>	<b>Heat Gun</b>	<p>Rated power input 2,000 W</p> <p>Weight without cable 0.9 kg</p> <p>Working temperature 50 - 630 °C</p> <p>Airflow 150 - 500 l/min</p> <p>Infinitely variable temperature control</p>
		<b>39</b>	<b>Soldering Stations</b>	<p>Tasks Supported Soldering</p> <p>Wattage 700W</p> <p>Input Voltage 220 → 240V</p> <p>Soldering Tip Temperature +480°C</p> <p>Number of Outputs 2</p> <p>Display Type LED</p> <p>1 x hot air gun</p> <p>1 x soldering iron</p> <p>1 x stand for soldering iron</p> <p>3 x nozzles</p>
		<b>40</b>	<b>Soldering Helping Hand</b>	<p>Main power supply 100 - 240 V/AC, 5 V/DC, 600 mA</p> <p>16 LEDs lighting</p> <p>360° rotating neck and bendable arms</p> <p>3.5 inch 2X Illuminated Helping Hand Magnifying Glass Station with 4X Auxiliary Lens</p> <p>2 fully adjustable helping hands , with clamp and alligator clips</p> <p>iron holder, and tray</p>
		<b>41</b>	<b>Electronics Components</b>	<p><b>Breadboards</b> Branded</p> <p><b>#24 Solid Wire</b> Branded</p> <p><b>Soldering Lead</b> Branded</p> <p><b>Transistor, resistors, trimpots</b> Branded</p> <p><b>ldr, etc</b> Branded</p>



				<b>Small Side Cutters</b> Branded <b>Small Half-round Nose Pliers</b> Branded <b>Wire Strippers</b> Branded <b>Soldering Iron</b> Branded <b>Paper Cutters</b> Branded <b>Desoldering Pumps</b> Branded <b>Small Flat Screw Drivers</b> Branded <b>Small Philip Screw Drivers</b> Branded <b>Multimeters</b> Branded
<b>3</b>	<b>Musical Instruments</b>	<b>43</b>	<b>Amplifier</b>	
				<b>Stereo Mode (both channels driven)</b> 8Ω / FTC 20 Hz - 20 kHz / 0.1% THD      1050 W 8Ω / EIA 1 kHz / 0.1% THD                    1100 W 4Ω / FTC 20 Hz - 20 kHz / 0.1% THD      1600 W 4Ω / EIA 1 kHz / 0.1% THD                    1800 W 2Ω / FTC 20 Hz - 20 kHz / 1% THD        2000 W 2Ω / EIA 1 kHz / 1% THD                      2500 W
				<b>Bridge Mono Mode</b> 8Ω / FTC 20 Hz - 20 kHz / 0.1% THD      3200 W 8Ω / EIA 1 kHz / 0.1% THD                    3600 W 4Ω / EIA 1 kHz / 1% THD                      5000 W Signal to Noise (20 Hz - 20 kHz) 8Ω        > -100 dB Distortion (SMPTE-IM)                        < 0.02% Input Sensitivity at 8Ω                         1.42V (+5.3 dBu) Voltage Gain                                      64x (36 dB) Output Circuitry                                 Class H, 3-tier
				<b>Power Requirements</b> Typical, 1/8 power pink noise at 4Ω*      13.9 A Severe, 1/3 power pink noise at 4Ω*      26.9 A Supplied Plug Type, 100/120V                NEMA 5-20 Supplied Plug Type, 230V                      CEE7/7
				<b>Weight</b> Net    75 lbs (33.1 kg) Shipping    87 lbs (37.2 kg)
				<b>Distortion (typical)</b> 20 Hz - 20 kHz: 10 dB below rated power < 0.02% THD / 4Ω and 8Ω  1.0 kHz and below: full rated power < 0.02% THD / 4Ω and 8Ω
				<b>Frequency Response</b> 20 Hz - 20 kHz: +0/-1 dB    -3 dB points: 5 Hz and 50 kHz (LF filter bypassed / 8Ω)

				<b>Damping Factor (1 kHz and below)</b> > 250 at 8Ω
				<b>Input Impedance</b> 10k ohms unbalanced / 20k ohms balanced
				<b>Input Clipping</b> 6.4 Vrms (+18 dBu)
				<b>Cooling</b> Continuously variable speed back-to-front air flow
				<b>Connectors (each channel)</b> Input: Active balanced / 3-pin Euro style detachable terminal block a XLR (pin 2+)
				<b>Controls</b> Front: AC switch / Ch. 1 & 2 gain knob Rear: 10-position DIP switch
				<b>Indicators</b> Power-on: Green LED / Signal: Yellow (1 per channel) / Clip: Red LED (1 per channel) Protect: Red LED Power-on: Green LED / Signal: Yellow (1 per channel) / Clip: Red LED (1 per channel) Protect: Red LED
				<b>Amplifier Protection</b> Full short circuit, open circuit, thermal, ultrasonic, RF protection. Stable into reactive or mismatched loads Full short circuit, open circuit, thermal, ultrasonic, RF protection. Stable into reactive or mismatched loads
				<b>Load Protection</b> Turn-on/off muting / AC coupling (850, 1450) / Triac crowbar (1850HD, 2450, 4050HD, 5050) on each channel Turn-on/off muting / AC coupling (850, 1450) / Triac crowbar (1850HD, 2450, 4050HD, 5050) on each channel
				<b>Dimensions</b> 5.25" (13.3 cm) tall / 3 rack spaces 5.25" (13.3 cm) tall / 3 rack spaces
				<b>Power Requirements</b> 100, 120, 230 VAC, 50 - 60 Hz (factory configured) 100, 120, 230 VAC, 50 - 60 Hz (factory configured)
		<b>44</b>	<b>Bass Guitar</b>	
				<b>General</b> Construction: Bolt-on Scale Length: 25-1/2" (648.0mm)
				<b>Body:</b> Body Materials: Alder Body Finish: Polyester
				<b>Neck:</b> Neck Materials: Maple Neck Finish: Satin Finish Fingerboard Materials: Rosewood or Laurel Fingerboard Radius: 13-3/4" (350mm)

				<p>Fret wire: Medium  Number of frets: 24  Nut materials: Locking Nut  Neck Width @ 0 Fret / 12th Fret:43.0 / 52.5 mm  Thickness @1st Fret / 12th Fret:19.0 / 21.7 mm</p>
				<p><b>Electronics:</b>  Neck Pickup: Humbucker/Ceramic  Middle Pickup: -  Bridge Pickup: Humbucker/Ceramic  Controls: Master Volume, Master Tone  Pickup Switch: 3-Position Lever Switch</p>
				<p><b>Hardware:</b>  Bridge :Locking Tremolo  Tremolo Arm: Φ6(Slot-in)  String spacing: 10.8mm  Tailpiece: -  Tuning Machines: Die-Cast  Pickguard: -</p>
				<p><b>Others:</b>  String gauge: D'Addario EXL120 / 0.009-0.042  Case: Gig Bag</p>
		<b>45</b>	<b>Digital Sound Mixer</b>	
				<p>Microphone input: Electronically balanced  Frequency Response to direct Output: 20Hz~100KHz at 0dBu ±1.5dB  Frequency Response to Main Output(48K): 20Hz~20KHz at 0dBu ±1.5dB  Frequency Response to Main Output(96K): 20Hz~20KHz at 0dBu ±1.5dB</p>
				<p>Distortion(THD&amp;N) to direct Output: &lt;0.0005% at 0dBu 1KHz  Distortion(THD&amp;N) to Main Output(48K): &lt;0.01% at 0dBu 1KHz  Distortion(THD&amp;N) to Main Output(96K): &lt;0.01% at 0dBu 1KHz</p>
				<p>SNR(Signal to Noise Ratio): 107dB  Maximum Input Level: +22dBu  Phantom Power(+/-3V): +48VDC  Line input: Unbalanced</p>
				<p>Frequency Response to direct Output: 20Hz~100KHz at 0dBu ±1.5dB  Frequency Response to Main Output(48K): 20Hz~20KHz at 0dBu ±1.5dB  Frequency Response to Main Output(96K): 20Hz~20KHz at 0dBu ±1.5dB  Distortion(THD&amp;N) to direct Output: &lt;0.0005% at 0dBu 1KHz  Distortion(THD&amp;N) to Main Output(48K): &lt;0.01% at 0dBu 1KHz  Distortion(THD&amp;N) to Main Output(96K): &lt;0.01% at 0dBu 1KHz  Gain: -15dBu~+35dBu  Maximum Input Level(Gain at 0dBu): +20dBu  AUX1~2 input: Balanced(2 stereo pair)</p>

				<p>Frequency Response to Main Output(48K): 20Hz~20KHz at +4dBu ±1.5dB</p> <p>Frequency Response to Main Output(96K): 20Hz~20KHz at +4dBu ±1.5dB</p> <p>Distortion(THD&amp;N) to Main Output(48K): &lt;0.01% at 0dBu 1KHz</p> <p>Distortion(THD&amp;N) to Main Output(96K): &lt;0.01% at 0dBu 1KHz</p> <p>Gain: -8 to +10dBu</p> <p>Maximum Input Level: +22dBu</p>
				<p><b>Tape L/R input:</b></p> <p>Frequency Response to Main Output(48K): 20Hz~20KHz at +4dBu ±1.5dB</p> <p>Frequency Response to Main Output(96K): 20Hz~20KHz at +4dBu ±1.5dB</p> <p>Distortion(THD&amp;N) to Main Output(48K): &lt;0.01% at 0dBu 1KHz</p> <p>Distortion(THD&amp;N) to Main Output(96K): &lt;0.01% at 0dBu 1KHz</p> <p>Gain: -8 to +10dBu</p> <p>Maximum Input Level: +22dBu</p>
				<p><b>Talkback MIC:</b></p> <p>Frequency Response to Main Output(48K): 20Hz~20KHz at +4dBu ±1.5dB</p> <p>Frequency Response to Main Output(96K): 20Hz~20KHz at +4dBu ±1.5dB</p> <p>Distortion(THD&amp;N) to Main Output(48K): &lt;0.01% at 0dBu 1KHz</p> <p>Distortion(THD&amp;N) to Main Output(96K): &lt;0.01% at 0dBu 1KHz</p> <p>Gain: -8 to +10dBu</p> <p>Phantom Power(+/-3V): +48VDC</p>
				<p><b>Main outputs:</b></p> <p>Maximum Output Level: +21dBu</p>
				<p><b>AUX1~8 Outputs:</b></p> <p>Maximum Output Level: +21dBu</p>
				<p><b>SUB1~4 Outputs:</b></p> <p>Maximum Output Level: +21dBu</p>
				<p><b>Tape Outputs :</b></p> <p>Maximum Output Level: +16dBu</p>
				<p><b>Control Room Outputs:</b></p> <p>Maximum Output Level: +20dBu</p>
				<p><b>System Crosstalk:</b></p> <p>Input to Output(at +4dBu 1KHz): -83dBu</p> <p>Adjacent Channels(at +4dBu 1KHz): -82dBu</p> <p>Noise(Bus noise): -85dBu</p>
				<p><b>Noise Gate:</b></p> <p>Threshold Range: -84dBu - 0dB</p>

				<p>Attack time: 0.5mS ~ 200mS Release time: 5mS~2S</p>
				<p><b>Compressor:</b> Threshold Range: -30dBu - +20dB Attack time: 10mS ~ 150mS Release time: 10mS~1S Ratio: 1:1 to 24:1 Gain: 0dBu - +24dB</p>
				<p><b>EQ:</b> Low (LowPass or LowShelf): 21Hz~19.2KHz +/- 24dB Low Mid: 21Hz~19.2KHz +/- 24dB High Mid: 21Hz~19.2KHz +/- 24dB High(HighPass or HighShelf): 21Hz~19.2KHz +/- 24dB</p>
				<p><b>Digital Audio:</b> ADC Dynamic Range: 114dB DAC Dynamic Range: 114dB Internal Processor: 32-bit , floating point ADC,DAC bit depth: 24bit</p>
				<p><b>Impedances:</b> Microphone input: 1.4KO Channel Insert return: 2.5KO All other inputs: 10KO or greater Tape out: 1KO All other output: 1200</p>
		<b>46</b>	<b>Electric Drumset</b>	
				<p>Kit configuration      Drum sound module: TD-17 x 1 Snare: PDX-12 x 1 Tom: PDX-8 x 3 Hi-Hat: CY-5 x 1 Hi-Hat control pedal: FD-9 x 1 Crash: CY-8 x 1 Ride: CY-8 x 1 Kick: KD-10 x 1 Drum Stand</p>
				<p>Extra trigger input jack      2 (CRASH 2, AUX)</p>
				<p>Accessories      Sound module mount AC adaptor Special connection cable Drum key Knob bolt (for PDX-12) Setup guide Owner's manuals</p>

For the information and guidance of all concerned.

A handwritten signature in black ink, appearing to read 'SEVEDEO J. MALATE', written over a circular stamp or watermark.

**SEVEDEO J. MALATE**

Chairman, Bids and Awards Committee